


## Product Description

Name: 3H-indolium, 2-[2-[2-chloro-3-[(1,3-dihydro-1,3,3-trimethyl-2H-indol-2-ylidene)ethylidene]-1-cyclohexen-1-yl]ethenyl]-1,3,3-trimethyl-, butyltriphenylborate

CAS # not available

Formula: C<sub>54</sub>H<sub>60</sub>ClBN<sub>2</sub>

Synonyms: H-Nu 780




- H-Nu 780 can cure a wide range of acrylate resins via **free-radical** mechanism.
- H-Nu 780 is a commercial photoinitiator with a broad absorbance range of 650 nm to 810 nm ( $\lambda_{\text{max}} = 791\text{nm}$  in DMSO).

## Advantages

- ✓ Good solubility in a variety of monomers
- ✓ Capable of curing a wide range of acrylates via free-radical mechanism
- ✓ Cure with infrared source (red handheld lasers and laser diodes)
- ✓ Cure through colored substrates (e.g. a red taillight assembly)
- ✓ Initiator bleaching upon light interaction can act as cure indicator (Borate V enhances cure and bleaching)

## Typical Properties

Property	Test Method	Typical Value
Absorbance Maximum	UV Visible spectroscopy	791 nm
Appearance	Visual	Dark Green Powder



## Applications Recommendations

- ✓ The recommended starting level of H-Nu 780 ranges from 0.15 to 1 wt.% in relation to the total amount of resin in a formulation.
- ✓ **Borate V** co-initiator at a 1:1 weight ratio is required. Additional amount of Borate V will increase the cure speed with and overall bleaching of the initiator in many formulations, so it is highly recommended.
- ✓ The H-Nu 780 is quite soluble in most acrylate resins, but it is recommended to predissolve photoinitiator and the Borate V (poor solubility in acrylates) in DMAA (N,N-Dimethylacrylamide, 2-3%) for ease of incorporation into your formulation.

## Disclaimer

The materials in this brochure are not intended for use in products which would be regulated by the Food and Drug Administration (FDA) unless the finished product is tested in accordance with the applicable safety requirements. Spectra Photopolymers is not able to recommend these materials for such uses and assumes no liability for any such use. Technical advice furnished by the seller shall not constitute a warranty or condition, statutory or otherwise, which is expressly disclaimed, all such advice being given and accepted is at the buyer's risk. Data and results that the user or buyer achieves may differ. Optimization, scale-up and product performance are the responsibility of the buyer or user.